Annals of R.S.C.B., ISSN:1583-6258, Vol. 25, Issue 4, 2021, Pages. 15623 - 15630
Received 05 March 2021; Accepted 01 April 2021.

High-Frequency Resonance Analysis and Stabilization Control Strategy of Modular Multilevel Converter Based on Eigenvalue Method

SathishKumarS[1],Lal Raja Singh.R[2],Ramesh M[3],RajeshKannanM[4],Arun Kumar P[5], Sivachitra.M[6]

[1]Associate Professor, Department of Electrical and Electronics Engineering, M.Kumarasamy College of Engineering, Karur, Tamilnadu.E.mail:sathishphd2k17@gmail.com
[2]Professor,Department of Electrical and Electronics Engineering, Kit-Kalaignar Karunanithi Institute of Technology,Coimbatore, Tamilnadu.E.mail:lalrajasingh@gmail.com
[3]UG Scholar, Department of Electrical and Electronics Engineering, M.Kumarasamy College of Engineering, Karur, Tamilnadu.E.mail:rameshmrameshm2618@gmail.com
[4]UG Scholar, Department of Electrical and Electronics Engineering, M.Kumarasamy College of Engineering, Karur, Tamilnadu.E.mail:rajeshm2904@gmail.com
[5]UG Scholar, Department of Electrical and Electronics Engineering, M.Kumarasamy College of Engineering, Karur, Tamilnadu.E.mail:p.arunkumarsvm@gmail.com
[6]Professor, Department of Electrical and Electronics Engineering, Kongu Engineering College,Perundurai, Tamilnadu.E.mail:siva.chitra3@gmail.com.

,

Abstract --- Another arrangement and its control technique for a Modular MultilevelConverter(MMC)-basedPhotoVoltaic(PV)-BatteryEnergyStorage(BES)structure.The proposed structure includesMMC high-repeat resonation wonder isusedinhighvoltageapplications(HVDCapplications,energyaccumulatingapplication).The proposed cream power dumbfound removal methodology uses BESsystemsanddifferentialstreamstocompensatepowerfumblesandmovepowerbetween the arms and legs of the converter. The state-space model of MMC controllerforpowercontrolissetupaccordingtothesensibleplanning.Bythenthetimedeferral of data and yield is considered in the controller, and the Pade fitting in state-spacemodelsuitableto theeigenvalueprocedureis familiarwith theall out statespacemodelofMMC.Consideringtheproposedmodel,theMMChigh-repeatresonation wonder is analyzed by the eigenvalue technique, and the exactness of themodel is affirmed by amusement results. Likewise, it is shown that high time concedecauseshigh-repeatresonationintheMMCstructurereliantuponthehelpfactorandthe systemeigenvaluecourse.

Keyword - Modular Multilevel Converter, dynamic phasor, eigenvalue technique, high-recurrencereverberationinvestigation,high-recurrence reverberationconcealment.

1. Introduction

At present, the impedance examination based strategy and eigenvalue based techniqueare the primary ways to deal with investigate MMC high-recurrence swaying. Albeitthe actual significance is clear and the displaying interaction is straightforward inimpedance based strategy, the steadiness assessment isn't instinctive sometimes, andboundarychangescausetroubleinsoundnessexamination.The eigenvaluebasedtechnique cannot just straightforwardly judge the security of the framework, to bespecific, the recurrence of framework shakiness can be acquired through the fancifulpieceoftheeigenvalue,yetinadditiontheeigenvectorandinterestfactorofeigenvalue can likewise givemore data.Since the three-stage voltage and currentdon't have consistent state esteems, eigenvalue investigation can'tbe acted in theMMC framework[1]. In this way, it is important to change the time-shifting frameworkintoastraighttime-

Annals of R.S.C.B., ISSN:1583-6258, Vol. 25, Issue 4, 2021, Pages. 15623 - 15630
Received 05 March 2021; Accepted 01 April 2021.

invariant(LTI)frameworkwithasteadyconsistentstateanincentive for examination. The two-level converter can be straightforwardly displayedin the simultaneous pivoting d-q-0 facilitate framework through state-space averagingstrategy. Nonetheless, there is a second consonant segment in the inside elements ofMMC,whichinfluencesitsdynamicattributes[2].

2. RelatedWork

In the MMC-based PV-BES structure, each PV sub module is interfaced from its dc side withvariousPVgenerators usingkepttwofoldpowerful expansion (DAB)dc-dc converters.Tomitigate tremendous power confounds which are outside the power rating of the BES systems,the proposed technique uses a blend of power exchange with BES structures and power movebetween the legs of the converter[3]. The embedded BES systems are used to smooth the yieldpower of the PV generators and cutoff the speed of progress of the power passed on to the hostgrid. The embedded BES structures are used to smooth the made power of the PV generators.Essential moving ordinary (SMA) methodology is applied to choose the proportion of powerthat the BES systems need to acclimatize or implant to confine the speed of progress of thepower passed on to the host organization[4-5]. The difference between the all out delivered powerof the PV generators andthe yield of the SMAisusedasthe power referenceofthe BESstructures. The reference BES power is isolated also between the BES systems, making themparticipate likewisein limitingthe speedof progressofthe powerpassed on to the hostnetwork[6-9].

3. ProposedSystem

This paper initially depicts the activity rule of the MMC. Further the numericaldisplaying isappeared. In this manner a methodology for reenactment of MMCs in an electromagnetictransient (EMT) reproduction program is introduced. This methodology is appropriate in anyevent, for MMCs with an enormous number of submodules[10-16]. At last a control arrangement ofthe MMC is talked about[17][18][19]. This segment incorporates block graphs for current regulators,dynamic force, and AC voltage greatness control. In ordinaryactivity, just one of the valves isturned on at a given moment on schedule. Contingentupon the current course the capacitor cancharge or release. At the point when just a single IBGT is turned on, either that IGBT or thefreewheelingdiodeinasimilarvalve willlead,contingentuponthecurrentcourse,andconsequently it bodes well tocharacterize a valve as on, demonstrating that either the IGBT orthediodeisdirecting, TheSubmoduleCircuitThreepotentialexchangingstatescanbecharacterized. The submodule yield voltage, VS M, approaches the capacitor voltage, VC, andthe capacitor charges if the multivalve current is positive and releases in any case. In the OFFor skirted state T2 is on,and T1 is off. The submodule yield voltage, VS M, is zero and thecapacitor voltage is consistent, for example the capacitor won't charge nor release. Inthehindered state, the two valves are off, and the current can just lead through the freewheelingdiodes. The capacitor will charge if the current is positive, however preferably it can't release.Theimpedingvoltageineachstageunitis doublethe DC voltage. This can be explainedfrom the condition when all the submodules in the upper multivalve are evaded, giving a phasevoltage comparable to the DC voltage. The lower multivalve should have the option to impedethe voltage across itself, for example theDC voltage. The outcome is that each switch shouldhave the option to obstruct the DC voltage, UD, partitioned by the quantity of submodules ineachmultivalve,N,giving Vsquare=UDN.Thecapacitorsinthelowermultivalvewilllikewise share the DC voltage and should be dimensioned similarly as the IGBTs. Consideringasimilarcase andanegativeIS McomparativewithI,eachIGBTintheuppervalveshouldhavethe

Annals of R.S.C.B., ISSN:1583-6258, Vol. 25, Issue 4, 2021, Pages. 15623 - 15630
Received 05 March 2021; Accepted 01 April 2021.

optiontoobstructthevoltageacrossthecapacitorintheequivalentsubmodule.Thisis onereasonwhycapacitorvoltageadjustingissignificant.Boththeupperandthelowermultivalveoughttocons istentlyhavealargeportionoftheDCconnectvoltageasnormalworthtogetastageyieldwithzeroDCcount erbalance.Themultivalvemaytakeanyadequacy among nothing and the DC voltage. The amount of embedded submodules in a stageis consistent, so embedding a submodule on one multivalve is done at the same time as bypassingoneintheothermultivalveofasimilarstage as shown in figure.1and circuit diagram are shown in figure.2.Figure 3 and 4 shows the simulation results. The proposed system experimental setup and visual representation are shown in figure.5&6.




Figure.1BlockDiagram of the proposed system




Figure2CircuitDiagramOf the proposed system

Annals of R.S.C.B., ISSN:1583-6258, Vol. 25, Issue 4, 2021, Pages. 15623 - 15630
Received 05 March 2021; Accepted 01 April 2021.

3.1 SoftwareSpecification

 MATLABprovideinteractivetoolsandcommandlinefunctionsfordataanalysisoperation,including:

- Interpolatinganddecimating
- Extractingsectionsofdata,scaling,andaveraging
- Thresholdingandsmoothing
- Correlation,Fourier analysis, and filtering
- 1-Dpeak,valley,andzerofinding
- Basicstatisticsandcurvefitting
- Matrixanalysis




Figure3SimulationResult– Constant




Figure4SimulationResult0

Annals of R.S.C.B., ISSN:1583-6258, Vol. 25, Issue 4, 2021, Pages. 15623 - 15630
Received 05 March 2021; Accepted 01 April 2021.

4. ComponentsRequired

1. PICMicrocontroller –PIC16F72
2. Resisters
3. PowerSupplyCircuit
4. Rectifier
5. Resistor
6. Capacitor
7. MOSFET
8. SolarPanel




Figure.5Experimental test setupofourSystem

Annals of R.S.C.B., ISSN:1583-6258, Vol. 25, Issue 4, 2021, Pages. 15623 - 15630
Received 05 March 2021; Accepted 01 April 2021.




Figure .6 OutputVisualRepresentationofourSystem

5. Conclusion

In this paper, the state-space model of MMC is set up dependent on the dynamicphasor strategy. To investigate the high recurrence reverberation of MMC framework,Pade guess is utilized to display the time delay in information and yield of MMCregulator, and the eigenvalue technique is utilized to examine the framework in detail.the framework may prompt about 1.8 kHz high-recurrence reverberation, which isreliable with the deficiency circumstance of Yue HVDC project. Through interestfactor investigation and root locus examination, the time deferral of receptive forcecontrolconnectlargelyaffectshighrecurrencereverberationthandynamicforcecontrol interface. At that point, the consequences of the coupling investigation of theinformation and yield time deferral of MMC regulator shows that the two are directlyconnected, yet additionally the four postponements produced by the partition of d-qpivot are around pairwise straight associated. The outer absolute time postponementcan be identical to the inside deferral of the regulator. At last, a defer pay controlsystem dependent on the Pade guess is proposed. Beginning from the key affectingcomponent of high recurrence shakiness, time delay, this methodology basically stiflesthe high recurrence reverberation produced by the MMC framework. It has a decentimpactand canbe joinedwith thecustomarydamping concealmenttechniquetoimprove the high-recurrence reverberation smothered. The following work can zero inon the ideal boundary plan and design advancement of control procedure, and attempttoutilizetimedeferraltostiflethehighrecurrencereverberationofMMCframework.

References

[1] H.Saad,Y.Fillion,S.Deschanvres,Y.VernayandS.Dennetiere,"Onresonances and music in HVDC-MMC station associated with AC network",IEEE Trans.ForceDel.,vol.32,no.3,pp.1565-1573,Jun.2017.

[2] J.SunandH.Liu,"Successionimpedancedemonstratingofmeasuredstaggered converters", IEEE J. Emerg. Sel. Themes Power Electron., vol. 5, no.4,pp.1427-1443,Dec. 2017.

[3] Bergna-Diaz, J. Freytes, X. Guillaud, S.

Annals of R.S.C.B., ISSN:1583-6258, Vol. 25, Issue 4, 2021, Pages. 15623 - 15630
Received 05 March 2021; Accepted 01 April 2021.

D'Arco and J. A. Suul, "Summed upvoltage-based state-space displaying of measured staggered converters withconsistent balance in consistent state", IEEE J. Emerg. Sel. Themes PowerElectron.,vol.6,no.2,pp.707-725,Jun.2018.

[4] J.Lyu,X.Zhang,X.Cai and M.Molinas, "Symphonious state-space basedlittle sign impedance demonstrating of a secluded staggered converter withthought of inside consonant elements", IEEE Trans. Force Electron., vol.34,no.3,pp.2134-2148,Mar.2019.

[5] X. Lu, X. Wang and W. Lin, "Exploration on little sign demonstrating and littlesign soundness for half and half secluded staggered converter", Proc. CSEE,vol.39,no.24,pp. 7286-7298,Dec.2019.

[6] T. Yin, Y. Wang, X. Wang, B. Yue, D. Zhao, J. Sun, et al., "Displaying andinvestigationofhigh-recurrenceMMCimpedancethinkingaboutvariouscontrol modes and voltage feedforward", IEEE Access, vol. 8, pp. 218575-218584,2020.

[7] S. Zhu, K. Liu, L. Qin, X. Ran, Y. Li, Q. Huai, et al., "Diminished requestdynamic model of particular staggered converter in lengthy timespan scale anditsapplicationinpowerframeworklow-recurrenceswayingexamination",IEEE Trans.ForceDel.,vol.34,no.6,pp.2110-2122,Dec.2019.

[8] Y.Zhang,C.Hong,L.Tu,T.ZhouandJ.Yang,"Explorationonhigh-recurrence reverberation component and dynamic symphonious concealmentprocedure of force frameworks with power hardware", Proc. Int. Conf. ForceSyst.Technol.(POWERCON),pp.2350-2356,Nov.2018.

[9] X. Guo, Z. Liu, Y. Li and Y. Lu, "Trademark examination of high recurrencereverberation of adaptable high voltage directmomentum and exploration onitsdampingcontrolmethodology", Proc.CSEE, vol. 40,no.4,pp.19-29,2019.

[10] Sathish Kumar Shanmugam , Karthikeyan Muthusamy, Vijayachitra Chennippan, Suresh Balasubramaniam , Sampathkumar Ramasamy , Saravanan Subramanian Modelling Of Solar Photovoltaic Array Fed Brushless Dc Motor Drive Using Enhanced Dc-Dc Converter Proceedings Of The Romanian Academy, Series a Volume 20, Number 2/2019, Pp. 169–178.

[11] Shanmugam Sathish Kumar, Arumugam Senthilkumar, Palanirajan Gowtham, Ramachandran Meenakumari, Kanagaraj Krishna Kumar Implementation of solar photovoltaic array and battery powered enhanced DC-DC converter using B4-inverter fed brushless DC motor drive system for agricultural water pumping applications. Journal of Vibroengineering, Vol. 20, Issue 2, 2018, p.1214-1233. https://doi.org/10.21595/jve.2018.19449

[12] Shanmugam Sathish Kumar, Senthilkumar Arumugam Design and implementation of DC source fed improved dual-output buck-boost converter for agricultural and industrial applications.
Journal of Vibroengineering, Vol. 19, Issue 8, 2017, p. 6433-6454. https://doi.org/10.21595/jve.2017.19228.

[13] Shanmugam, S.K., Ramachandran, M., Kanagaraj, K.K. and Loganathan, A. (2016) Sensorless Control of Four-Switch Inverter for Brushless DC Motor Drive and Its Simulation.Circuits and Systems, 7, 726-734. http://dx.doi.org/10.4236/cs.2016.76062

[14] V. Krishnaveni, K. Kiruthika and S. S. Kumar, "Design and implementation of low cost four switch inverter for BLDC motor drive with active power factor correction," 2014 International Conference on Green Computing Communication and Electrical Engineering (ICGCCEE), Coimbatore, India, 2014, pp. 1-7, doi: 10.1109/ICGCCEE.2014.6922424.

[15] Sathishkumar S., Meenakumari R., Jobanarubi E., Anitta P.J.S., Ravikumar P. (2015) Microcontroller Based BLDC Motor Drive for Commercial Applications. In: Kamalakannan C., Suresh L., Dash S., Panigrahi B. (eds) Power Electronics and Renewable Energy Systems. Lecture Notes in Electrical Engineering, vol 326. Springer, New Delhi. https://doi.org/10.1007/978-81-322-2119-7_81

[16] Meenakumari Ramachandran Sathishkumar Shanmugam Design and Implementation of

Embedded Processor Based Brushless Motor Drive using Lead Acid Battery as Source with Lithium Ion Capacitor, Indonesian Journal of Electrical Engineering and Computer Science,Volume 14 Issue 3 Pages 455-469.

[17] Punithavathani, D. Shalini, K. Sujatha, and J. Mark Jain. "Surveillance of anomaly and misuse in critical networks to counter insider threats using computational intelligence." Cluster Computing 18.1 (2015): 435-451.

[18] Chang, Jinping, Seifedine Nimer Kadry, and Sujatha Krishnamoorthy. "Review and synthesis of Big Data analytics and computing for smart sustainable cities." IET Intelligent Transport Systems (2020).

[19] Song, Hesheng, and Carlos Enrique Montenegro-Marin. "Secure prediction and assessment of sports injuries using deep learning based convolutional neural network." Journal of Ambient Intelligence and Humanized Computing 12.3 (2021): 3399-3410.